



Expanding Your Solutions

**Corporate Headquarters**  
13191 Crossroads Pkwy N., Ste 325  
City of Industry, CA 91746  
Phone: 800.775.2362  
Fax: 626.330.7598  
www.cemcosteel.com

**Manufacturing Facilities**  
City of Industry, CA  
Denver, CO  
Ft. Worth, TX  
Pittsburg, CA

**Structural Engineering/Design**  
1001-A Pittsburgh Antioch Hwy  
Pittsburg, CA 94565  
Phone: 800.775.2362  
Fax: 626.330.7598  
www.cemcoengineering.com

**Technical Services**  
13191 Crossroads Pkwy N., Ste 325  
City of Industry, CA 91746  
Phone: 800.416.2278  
Fax: 626.249.5004

## 800S200-118 • C-STUD 118 MIL (10 GA.)

### Geometric Properties

800S200-118 "S" structural load-bearing studs are produced from hot-dipped galvanized steel in standard CP60 coating. CP90 is available upon special request, and may require up-charges and extended lead times.

### Physical Properties

| Model No.   | Design Thickness (in.) <sup>1</sup> | Minimum Thickness (in.) <sup>2</sup> | Yield (ksi) | Coating <sup>3,4</sup> | Web Depth (in) | Flange Size (in) | Lip (in) |
|-------------|-------------------------------------|--------------------------------------|-------------|------------------------|----------------|------------------|----------|
| 800S200-118 | 0.1242                              | 0.1180                               | 50          | CP60                   | 8              | 2                | 1        |

**Notes:**

1. Uncoated steel thickness. Thickness is for carbon sheet steel.
2. Minimum thickness represents 95% of the design thickness and is the minimum acceptable thickness.
3. Per ASTM C955 & A1003, Table 1.
4. CP90 available upon request. Will require extended lead time and upcharge.

**Color Code (painted on ends):** 118-mil: Blue

### ASTM & Code Standards:

- ASTM A653/A653M, A924/A924M, A1003/1003, C955 & C1007
- ICC-ES & SFIA Code Compliance Certification Program
- ICC ESR-3016
- ATI CCRR-0224
- IBC: 2012, 2015, 2018
- CBC: 2013, 2016
- AISI: S100-07, S100-12, S100-16, S200-12, S240-15


### LEED v4 for Building and Design Construction

- MR Prerequisite: Construction and Demolition Waste Management Planning.
- MR Credit: Construction and Demolition Waste Management.
- MR Credit: Building Product Disclosure and Optimization – Sourcing of Raw Materials, Option 2.
- MR Credit: Building Product Disclosure and Optimization – Environmental Product Declarations, Options 1 & 2.
- MR Credit: Building Product Disclosure and Optimization – Material Ingredients, Option 1.
- MR Credit: Building Life-Cycle Impact Reduction, Option 4.

### CEMCO cold-formed steel framing products contain 30% to 37% recycled steel.

- Total Recycled Content: 36.9%
- Post-Consumer: 19.8%
- Pre-Consumer: 14.4%

**CSI Division:** 05.40.00 – Cold-Formed Metal Framing



### Hole Detail

| Standard hole centers are 24" | (Z) (in) | (Y) (in) |
|-------------------------------|----------|----------|
| 2-1/2" studs                  | 2.000"   | 0.750"   |
| 3-1/2" to 14" stud            | 3.250"   | 1.500"   |

### 800S200-118 Section Properties

| Design Thickness (in.) | Fy (ksi) | Gross <sup>3</sup>    |                       |         |                       |         | Effective Properties <sup>2</sup> |                       |           |          |            |            | Torsional Properties      |                       |         |        |         | Lu (in) |      |
|------------------------|----------|-----------------------|-----------------------|---------|-----------------------|---------|-----------------------------------|-----------------------|-----------|----------|------------|------------|---------------------------|-----------------------|---------|--------|---------|---------|------|
|                        |          | Ix (in <sup>4</sup> ) | Sx (in <sup>3</sup> ) | Rx (in) | Iy (in <sup>4</sup> ) | Ry (in) | Ix (in <sup>4</sup> )             | Sx (in <sup>3</sup> ) | Ma (in-k) | Vag (lb) | Vanet (lb) | Mad (in-k) | Jx1000 (in <sup>4</sup> ) | Cw (in <sup>6</sup> ) | Xo (in) | m (in) | Ro (in) |         | β    |
| 0.1242                 | 50       | 13.316                | 3.329                 | 2.949   | 0.665                 | 0.659   | 13.316                            | 3.329                 | 117.953   | 16235    | 7115       | 117.55     | 7.872                     | 8.981                 | -1.188  | 0.764  | 3.247   | 0.866   | 36.5 |

**Notes:** 1. Web depth for track sections equals nominal depth plus 2 times the design thickness plus bend radius. 2. The values are for members with punch-outs. 3. Gross properties are based on the full, unreduced cross-section, away from web punchouts. 4. Use the effective moment of inertia for deflection calculation. 5. Allowable moment is lesser of Ma and Mad. Distortional buckling is based on an assumed  $K\phi = 0$ . 6. These members are available un-punched only.

Check the updated list of Certified Production Facilities at Intertek's website at <http://www.intertek.com/building/sfia>



This technical information reflects the most current information available and supersedes any and all previous publications effective December 04, 2018.

12-04-18 AT