



Expanding Your Solutions

**Corporate Headquarters**  
13191 Crossroads Pkwy N., Ste 325  
City of Industry, CA 91746  
Phone: 800.775.2362  
Fax: 626.330.7598  
www.cemcosteel.com

**Manufacturing Facilities**  
City of Industry, CA  
Denver, CO  
Ft. Worth, TX  
Pittsburg, CA

**Structural Engineering/Design**  
1001-A Pittsburgh Antioch Hwy  
Pittsburg, CA 94565  
Phone: 800.775.2362  
Fax: 626.330.7598  
www.cemcoengineering.com

**Technical Services**  
13191 Crossroads Pkwy N., Ste 325  
City of Industry, CA 91746  
Phone: 800.416.2278  
Fax: 626.249.5004

## 162VT300-30 VIPERTRACK

### Geometric Properties

1-5/8" ViperTrack with 3" legs is manufactured from standard G40 hot-dipped galvanized steel. G60 and G90 coatings are available through special order, and may require up-charges and extended lead times.

### Physical Properties

| Model No.   | Design Thickness (in) | Minimum Thickness (in) | Yield (ksi) | Coating <sup>3,4</sup> | Web Depth (in) | Leg Size (in) | GAP <sup>5</sup> (in) | Load <sup>5</sup> (lb.) | Max Height <sup>5</sup> 5 psf, 16" o.c. |
|-------------|-----------------------|------------------------|-------------|------------------------|----------------|---------------|-----------------------|-------------------------|-----------------------------------------|
| 162VT300-30 | 0.0312                | 0.0296                 | 33          | G40                    | 1-5/8          | 3             | --                    | --                      | --                                      |

**Notes:**

- Uncoated steel thickness. Thickness is for carbon sheet steel.
- Minimum thickness represents 95% of the design thickness and is the minimum acceptable thickness.
- Per ASTM C645 & A1003, Table 1.
- G60 and G90 available upon request. Will require extended lead time and upcharge.
- Use Gap, Load and Maximum Height data when member is used as a top deflection track.

**Color Code (painted on ends):** 30 mil: Pink

### ASTM & Code Standards:

- ASTM A653/A653M, A924/A924M, A1003/A1003M, C645, C754, E119
- IBC: 2015, 2018, 2021
- CBC: 2016, 2019, 2022
- AISI: S100, S220


### LEED v4 for Building and Design Construction

- MR Prerequisite: Construction and Demolition Waste Management Planning.
- MR Credit: Construction and Demolition Waste Management.
- MR Credit: Building Product Disclosure and Optimization – Sourcing of Raw Materials, Option 2.
- MR Credit: Building Product Disclosure and Optimization – Environmental Product Declarations, Options 1 & 2.
- MR Credit: Building Product Disclosure and Optimization – Material Ingredients, Option 1.
- MR Credit: Building Life-Cycle Impact Reduction, Option 4.

### CEMCO cold-formed steel framing products contain 30% to 37% recycled steel.

- Total Recycled Content: 36.9%
- Post-Consumer: 19.8%
- Pre-Consumer: 14.4%

**CSI Division:** 09.22.16 – Non-Structural Metal Framing



### ViperTrack 3.00" Leg

| Member      | Leg Size (in) | Gross Properties |             |          |             |                         |                                   |                                   |                     |                                   |                                   |                     | Effective Properties               |                                    |           | Torsional Properties |                                       |                     |                     |       |
|-------------|---------------|------------------|-------------|----------|-------------|-------------------------|-----------------------------------|-----------------------------------|---------------------|-----------------------------------|-----------------------------------|---------------------|------------------------------------|------------------------------------|-----------|----------------------|---------------------------------------|---------------------|---------------------|-------|
|             |               | Weight (lb/ft)   | Design (in) | Min (in) | Yield (ksi) | Area (in <sup>2</sup> ) | I <sub>x</sub> (in <sup>4</sup> ) | S <sub>x</sub> (in <sup>3</sup> ) | R <sub>x</sub> (in) | I <sub>y</sub> (in <sup>4</sup> ) | S <sub>y</sub> (in <sup>3</sup> ) | R <sub>y</sub> (in) | I <sub>xd</sub> (in <sup>4</sup> ) | S <sub>xe</sub> (in <sup>3</sup> ) | Ma (in-k) | X <sub>o</sub> (in)  | J <sub>x1000</sub> (in <sup>4</sup> ) | C <sub>w</sub> (in) | R <sub>o</sub> (in) | β     |
| 162VT300-30 | 3.00          | 0.90             | 0.0346      | 0.0329   | 33          | 0.264                   | 0.172                             | 0.192                             | 0.807               | 0.254                             | 0.139                             | 0.979               | 0.094                              | 0.068                              | 1.34      | -2.52                | 0.1050                                | 0.1490              | 2.82                | 0.202 |

**Notes:**

- Section properties are in accordance with AISI S100-16/S2-20.
- Cold-work of forming is not included.
- The effective moment of inertia for deflection is calculated based on AISI S100-16/S2-20 procedure 1 for serviceability determination.
- The center line bend radius is greater than 2 times the design thickness or 3/32".
- Web-to-thickness ratio exceeds 200.
- Web-to-thickness ratio exceeds 260.
- Flange-width-to-thickness-ratio exceeds 60, only gross properties will be determined.

Check the updated list of Certified Production Facilities at Intertek's website at <http://www.intertek.com/building/sfia>



This technical information reflects the most current information available and supersedes any and all previous publications effective September 25, 2023.  
09-25-23 AT