

| TABLE 1           |                            |                     |         |         |
|-------------------|----------------------------|---------------------|---------|---------|
| FLOOR JOIST DEPTH | MINIMUM BLOCKING THICKNESS | BLOCKING LENGTH     |         |         |
|                   |                            | FLOOR JOIST SPACING |         |         |
|                   |                            | 12"O.C.             | 16"O.C. | 24"O.C. |
| 8"                | 18GA. (43 MIL)             | 10"                 | 14"     | 22"     |
| 9.25"             | 18GA. (43 MIL)             | 10"                 | 14"     | 22"     |
| 10.00"            | 18GA. (43 MIL)             | 9 3/4"              | 13 3/4" | 21 3/4" |
| 11.25"            | 18GA. (43 MIL)             | 10"                 | 14"     | 22"     |
| 12.00"            | 16GA. (54 MIL)             | 9 3/4"              | 13 3/4" | 21 3/4" |
| 14.00"            | 16GA. (54 MIL)             | 9 3/4"              | 13 3/4" | 21 3/4" |

ATTACH CLIP TO JOIST & BLOCKING AS REQUIRED BY BUILDING CODE OR E.O.R.

ATTACH CEMCO SURE BRIDGING AS REQUIRED BY BUILDING CODE OR E.O.R.

PIECE OF CEMCO STUD OR TRACK BLOCKING TO MATCH DEPTH OF FLOOR JOIST, @ MAX 8'-0" O.C., BLOCKING THICKNESS BY DESIGN (SEE TABLE 1)

SIMPSON CLIP OR EQUIVALENT, EACH END (BY DESIGN)

CEMCO SURE BRIDGING

CEMCO SSCJ FLOOR JOISTS PER PLAN

