



NOTE: DOUBLE LAYERS OF 5/8" DRYWALL FOR 2 HOUR FIRE RATING

**HW-D-0515**

ASSEMBLY RATING: 1 HR

**STANDARD WALL, PERPENDICULAR TO FLUTED DECK**

DISCLAIMER:

CEMCO assumes no liability for failure resulting from the use of its drawings, computations, or for failure resulting from the use of alternate materials, or improper application or installation. This drawing is supplied solely to assist in the selection and application of CEMCO products. This drawing is generic in nature and should not be used in design or construction without an independent evaluation by a qualified Architect or Engineer of Record. All warranties of any kind, express or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose are disclaimed.

REVISION:

DRAWN BY: T. GARIBEKIAN  
 DATA: 03/31/2016  
 APPROVED BY: DON PILZ  
 DATE: 03/31/2016  
 SCALE: 3"=1'-0"  
 JOB NO.: UL DETAILS  
 SHEET NO.:

**SD145.1**



WWW.CEMCOSTEEL.COM

263 N. Covina Lane.  
 City of Industry, CA 91744  
 PHONE (800) 775-2362  
 ENG. DEPT.  
 FAX (626) 369-7243  
 WWW.CEMCOSTEEL.COM