



Expanding Your Solutions

**Corporate Headquarters**  
13191 Crossroads Pkwy N., Ste 325  
City of Industry, CA 91746  
Phone: 800.775.2362  
Fax: 626.330.7598  
www.cemcosteel.com

**Manufacturing Facilities**  
City of Industry, CA  
Commerce City, CO  
Ft. Worth, TX  
Pittsburg, CA

**Structural Engineering/Design**  
1001-A Pittsburgh Antioch Hwy  
Pittsburg, CA 94565  
Phone: 800.775.2362  
Fax: 626.330.7598  
www.cemcoengineering.com

**Technical Services**  
13191 Crossroads Pkwy N., Ste 325  
City of Industry, CA 91746  
Phone: 800.416.2278  
Fax: 626.249.5004

## 1200S300-118 • C-STUD 118 MIL (10 GA.)

### Geometric Properties

1200S300-118 "S" structural load-bearing studs are produced from hot-dipped galvanized steel in standard CP60 coating. CP90 is available upon special request, and may require up-charges and extended lead times.

### Physical Properties

| Model No.    | Design Thickness (in.) <sup>1</sup> | Minimum Thickness (in.) <sup>2</sup> | Yield (ksi) | Coating <sup>3,4</sup> | Web Depth (in) | Flange Size (in) | Lip (in) |
|--------------|-------------------------------------|--------------------------------------|-------------|------------------------|----------------|------------------|----------|
| 1200S300-118 | 0.1242                              | 0.1180                               | 50          | CP60                   | 10             | 3                | 7/8      |

**Notes:**

- Uncoated steel thickness. Thickness is for carbon sheet steel.
- Minimum thickness represents 95% of the design thickness and is the minimum acceptable thickness.
- Per ASTM C955 & A1003, Table 1.
- CP90 available upon request. Will require extended lead time and upcharge.

**Color Code (painted on ends):** 118-mil: Blue

**ASTM & Code Standards:**

- ASTM A653/A653M, A924/A924M, A1003/1003, C955 & C1007
- ICC-ES & SFIA Code Compliance Certification Program
- ICC ESR-3016
- ATI CCRR-0224
- IBC: 2015, 2018, 2021
- CBC: 2019, 2022
- AISI: S100, S200, S240


**LEED v4 for Building and Design Construction**

- MR Prerequisite: Construction and Demolition Waste Management Planning.
- MR Credit: Construction and Demolition Waste Management.
- MR Credit: Building Product Disclosure and Optimization – Sourcing of Raw Materials, Option 2.
- MR Credit: Building Product Disclosure and Optimization – Environmental Product Declarations, Options 1 & 2.
- MR Credit: Building Product Disclosure and Optimization – Material Ingredients, Option 1.
- MR Credit: Building Life-Cycle Impact Reduction, Option 4.

**CEMCO cold-formed steel framing products contain 30% to 37% recycled steel.**

- Total Recycled Content: 36.9%
- Post-Consumer: 19.8%
- Pre-Consumer: 14.4%

**CSI Division:** 05.40.00 – Cold-Formed Metal Framing



### 1200S300-118<sup>6</sup> Section Properties

| Design Thickness (in.) | Fy (ksi) | Gross <sup>3</sup>    |                       |         |                       |         | Effective Properties <sup>2</sup> |                       |           |          |            |            | Torsional Properties      |                       |         |        |         |       | Lu (in) |
|------------------------|----------|-----------------------|-----------------------|---------|-----------------------|---------|-----------------------------------|-----------------------|-----------|----------|------------|------------|---------------------------|-----------------------|---------|--------|---------|-------|---------|
|                        |          | Ix (in <sup>4</sup> ) | Sx (in <sup>3</sup> ) | Rx (in) | Iy (in <sup>4</sup> ) | Ry (in) | Ix (in <sup>4</sup> )             | Sx (in <sup>3</sup> ) | Ma (in-k) | Vag (lb) | Vanet (lb) | Mad (in-k) | Jx1000 (in <sup>4</sup> ) | Cw (in <sup>6</sup> ) | Xo (in) | m (in) | Ro (in) | β     |         |
| 0.1242                 | 50       | 45.106                | 7.518                 | 4.452   | 2.095                 | 0.959   | 45.106                            | 7.232                 | 243.67    | 14986    | ---        | 201.68     | 11.704                    | 60.251                | -1.666  | 1.071  | 4.849   | 0.882 | 53.0    |

**Notes:** 1. Web depth for track sections equals nominal depth plus 2 times the design thickness plus bend radius. 2. The values are for members with punch-outs. 3. Gross properties are based on the full, unreduced cross-section, away from web punchouts. 4. Use the effective moment of inertia for deflection calculation. 5. Allowable moment is lesser of Ma and Mad. Distortional buckling is based on an assumed  $K\phi = 0$ . 6. These members are available un-punched only.

Check the updated list of Certified Production Facilities at Intertek's website at <http://www.intertek.com/building/sfia>



This technical information reflects the most current information available and supersedes any and all previous publications effective May 1, 2024.

05/01/2024 AT