



Expanding Your Solutions

Corporate Headquarters
13191 Crossroads Parkway North, Suite 325
City of Industry, CA 91746
Phone: 800.775.2362
Fax: 626.330.7598

Manufacturing Facilities
City of Industry, CA
Denver, CO
Ft. Worth, TX
Pittsburg, CA

Structural Engineering/Design
1001-A Pittsburgh Antioch Hwy
Pittsburg, CA 94565
Phone: 800.775.2362
Fax: 626.330.7598

Technical Services
263 North Covina Lane
City of Industry, CA 91744
Phone: 800.416.2278
Fax: 626.249.5005

DIAMOND METAL LATH (EXPANDED) WITHOUT PAPER

Introduction

CEMCO's Diamond Metal Lath is a versatile base for cement plaster walls. Its carefully formed diamond keys allow for proper embedment and keying of the scratch coat on all types of walls. Can be used with hand and machine applied plaster. All CEMCO expanded metal lath is produced from standard G60 hot-dipped galvanized steel. G90 is available upon special request.

LWD = LONG WAY DIAMOND
SWD = SHORT WAY DIAMOND

Packaging

Weight per Square Yard (lb/yd ²)	Sheet Size	Pieces per bundle	Yards per Pallet
1.75	27.5" x 96"	10	1000
2.5	27.5" x 96"	10	1000
3.4	27.5" x 96"	10	1000

Note: 50 bundles per pallet.

ASTM's & Code Standards

- ASTM A653
- ASTM C841 (Installation)
- ASTM C847
- ASTM A924
- ASTM C1063 (Installation)
- ICC ESR-1623
- ANSI A42.3, ANSI A42.4
- U.S. HUD 4930.1

LEED v3 for Building and Design Construction


- MR Credit 2: Construction Waste Management.
- MR Credit 4: Recycled Content.

LEED v4 for Building and Design Construction


- MR Prerequisite: Construction and Demolition Waste Management Planning.
- MR Credit: Construction and Demolition Waste Management.
- MR Credit: Building Product Disclosure and Optimization – Sourcing of Raw Materials, Option 2.
- MR Credit: Building Product Disclosure and Optimization – Environmental Product Declarations, Options 1 & 2.
- MR Credit: Building Product Disclosure and Optimization – Material Ingredients, Option 1.
- MR Credit: Building Life-Cycle Impact Reduction, Option 4.

CEMCO cold-formed steel framing products contain 30% to 37% recycled steel.

- Total Recycled Content: 36.9%
- Post-Consumer: 19.8%
- Pre-Consumer: 14.4%



DETAIL A



Technical Services

Technical Services: 800.416.2278
Structural Engineering/Design: 925.473.9340
www.cemcosteel.com



This technical information reflects the most current information available and supersedes any and all previous publications effective August 1, 2016.

G040 Rev 3