



Expanding Your Solutions

Corporate Headquarters
13191 Crossroads Parkway North, Suite 325
City of Industry, CA 91746
Phone: 800.775.2362
Fax: 626.330.7598

Manufacturing Facilities
City of Industry, CA
Denver, CO
Ft. Worth, TX
Pittsburg, CA

Structural Engineering/Design
1001-A Pittsburgh Antioch Hwy
Pittsburg, CA 94565
Phone: 800.775.2362
Fax: 626.330.7598

Technical Services
263 North Covina Lane
City of Industry, CA 91744
Phone: 800.416.2278
Fax: 626.249.5005

SELF-FURRED METAL LATH (DIMPLED) WITH "D" PAPER

Introduction

CEMCO's Self Furred Diamond Metal Lath "Dimpled" is manufactured with 1/4" dimples in the lath. The dimples provide the necessary minimum 1/4" furring off the sheathing's surface to allow for proper embedment and keying of the scratch coat on all types of walls. This lath is available with Grade D asphalt paper backing. A saturated black asphalt paper complying with Federal Spec. No. UUB-790A Style 2 Grade D. Manufactured with a 3" lap for weathered application. D + D is double papered, as required in the Building Code: weather resistive barriers shall be installed when applied over wood based sheathing, shall include two layers of Grade "D" paper. All CEMCO expanded metal lath is produced from standard G60 hot-dipped galvanized steel. G90 is available upon special request.

Packaging

Weight per Square Yard (lb/yd ²)	Sheet Size	Pieces per bundle	Yards per Pallet
1.75	27.5" x 96"	10	500
2.5	27.5" x 96"	10	500
3.4	27.5" x 96"	10	500

Note: 25 bundles per pallet.

ASTM's & Code Standards

- ASTM A653
- ASTM C841 (Installation)
- ASTM C847
- ASTM A924
- ASTM C1063 (Installation)
- ICC ESR-1623
- Fed. Spec. QQ-1-101C and UUB-790A Style 2 Grade D (Paper)
- ANSI A42.3, ANSI A42.4
- U.S. HUD 4930.1

LEED v3 for Building and Design Construction


- MR Credit 2: Construction Waste Management.
- MR Credit 4: Recycled Content.

LEED v4 for Building and Design Construction



- MR Prerequisite: Construction and Demolition Waste Management Planning.
- MR Credit: Construction and Demolition Waste Management.
- MR Credit: Building Product Disclosure and Optimization – Sourcing of Raw Materials, Option 2.
- MR Credit: Building Product Disclosure and Optimization – Environmental Product Declarations, Options 1 & 2.
- MR Credit: Building Product Disclosure and Optimization – Material Ingredients, Option 1.
- MR Credit: Building Life-Cycle Impact Reduction, Option 4.

CEMCO cold-formed steel framing products contain 30% to 37% recycled steel.

- Total Recycled Content: 36.9%
- Post-Consumer: 19.8%
- Pre-Consumer: 14.4%



LWD = LONG WAY DIAMOND
SWD = SHORT WAY DIAMOND



Technical Services

Technical Services: 800.416.2278
Structural Engineering/Design: 925.473.9340
www.cemcosteel.com



This technical information reflects the most current information available and supersedes any and all previous publications effective August 1, 2016.