Head of Wall - Slotted Tracks by CEMCO

Health Product Declaration v2.1

created via: HPDC Online Builder

CLASSIFICATION: 05 40 00 Metals: Cold-Formed Metal Framing

PRODUCT DESCRIPTION: This HPD covers the following CEMCO Head of Wall products: "CST" and "SLP-TRK®" Slotted Slip Tracks; Exterior Slotted Track (EST); TAB TRACK. CEMCO's "CST" Brand slotted track and Sliptrack System's "SLP-TRK®" brand slotted track are evaluated and approved for use by ICC in report ESR-2012, and are available with optional drift slots. "CST" and "SLP-TRK®" are produced from G40 (18 and 33 mil) and G60 (43, 54, 68 mil) coated steel. CEMCO Exterior Slotted Track (EST) is a vertical deflection track member. The external groove provides a resting point for sheathing, transferring the weight of the sheathing to the framing member, and the 2" web slots provide drift movement capabilities. CEMCO EST is fabricated from hot-dipped galvanized steel complying with ASTM A653, and ASTM A1003 Structural Grade 50 Type H for Grade 33 Type H for with a minimum G60 coating, and complies with ASTM C645. CEMCO TAB TRACK provides a non mechanical (screwless) stud-to-track attachment for metal stud wall framing. A series of 1" long tabs are evenly spaced across the track's legs providing flexibility to regular and irregular layout. Once the studs are nested within the TAB TRACK, the tabs may be pushed inward on either side of the stud to prohibit lateral movement while maintaining vertical deflection. Available in 33 mil thicknesses, TAB TRACK is manufactured from G40 hot-dipped galvanized steel.



Section 1: Summary

Basic Method / Product Threshold

CONTENT INVENTORY

Inventory Reporting Format

Nested Materials Method

Basic Method

Threshold Disclosed Per

Material

Product

Threshold level

C 100 ppm

€ 1,000 ppm

C Per GHS SDS

C Per OSHA MSDS

C Other

Residuals/Impurities

Considered

C Partially Considered

C Not Considered

Explanation(s) provided for Residuals/Impurities?

• Yes • No

Are All Substances Above the Threshold Indicated:

Characterized

Yes ○ No

Percent Weight and Role Provided?

Screened

Yes ○ No

Using Priority Hazard Lists with Results Disclosed?

Identified

Yes ○ No

Name and Identifier Provided?

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

MATERIAL | SUBSTANCE | RESIDUAL OR IMPURITY

GREENSCREEN SCORE | HAZARD TYPE

HEAD OF WALL - SLOTTED TRACKS [STEEL NOGS ZINC LT-P1 | AQU | PHY | END | MUL

Number of Greenscreen BM-4/BM3 contents ... 0

Contents highest concern GreenScreen Benchmark or List translator Score ... LT-P1

Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

This Health Product Declaration (HPD) was completed in accordance with the HPD Standard version 2.1.1, and discloses hazards associated with all substances present at or above 1000 parts per million (ppm) in the finished product. Therefore, this HPD qualifies for the LEED v4 MR credit Building Product Disclosure and Optimization: Material Ingredient Reporting (Option 1).

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

VOC Content data is not applicable for this product category.

CERTIFICATIONS AND COMPLIANCE See Section 3 for additional listings.

VOC emissions: Inherently non-emitting source per LEED® Multi-attribute: Environmental Product Declaration (EPD) by UL

CONSISTENCY WITH OTHER PROGRAMS

Pre-checked for LEED v4 Material Ingredients, Option 1

Third Party Verified?

C Yes No

PREPARER: Self-Prepared

VERIFICATION #:

SCREENING DATE: 2018-10-10 PUBLISHED DATE: 2018-10-22 EXPIRY DATE: 2021-10-10



Section 2: Content in Descending Order of Quantity

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.1, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-1-standard

HEAD OF WALL - SLOTTED TRACKS

PRODUCT THRESHOLD: 1000 ppm

RESIDUALS AND IMPURITIES CONSIDERED: Yes

RESIDUALS AND IMPURITIES NOTES: Residuals and Impurities were "Considered", as outlined in Emerging Best Practices. No residuals or impurities are known or expected to be present at or above the Content Inventory Threshold indicated that have a GS score of BM-1, LT-1, LT-P1 or NoGS based on information provided in supplier SDS and as predicted by process chemistry (Pharos CML). However, supplier SDS states the following: "All commercial steel products may contain small amounts of various elements in addition to those specified. These small quantities (less than 0.1%) may exist as intentional additions, or as "trace" or "residual" elements that generally originate in the raw materials used. These elements may include: aluminum, antimony, arsenic, boron, cadmium, calcium, chromium, cobalt, columbium, copper, lead, molybdenum, nickel, silicon, tin, titanium, vanadium, and zirconium."

OTHER PRODUCT NOTES: Standard G40 and G60 hot-dipped galvanized steel. Passivation coatings for corrosion resistance are an industry standard for this type of material; however, the substances used for such coatings fall below the inventory threshold (0.1% or 1000 ppm) of the material, and are therefore not reported here.

STEEL					ID: 12597-69-2	
%: 97.4000 - 99.1000	GS: NoGS	RC: Both	nano: No	ROLE: Base Metal		
HAZARDS:	AGENCY(IES) WITH WARNINGS:					
None Found	No warnings found on HPD Priority lists					

SUBSTANCE NOTES: CEMCO cold-formed steel framing products contain 30% to 37% pre- and post-consumer recycled steel sourced from several domestic (USA) suppliers. Specific guidelines are being created to address known issues related to transparency and disclosure for several materials ("Special Conditions"), including Metal Alloys such as Steel. Supplier reports the following composition of alloying elements: max 0.9% Manganese (7439-96-5; LT-P1); max 0.6% Carbon (7440-44-0; LT-UNK); max 0.6% Silicon (7440-21-3; LT-UNK); max 0.5% Copper (7440-50-8; LT-UNK); max 0.15% Phosphorus (8049-19-2; NoGS); max 0.1% Calcium (7440-70-2; LT-P1).

ZINC				ID: 7440-66		
%: 0.9000 - 2.6000	GS: LT-P1	RC: None	nano: No	ROLE: Metallic Coating		
HAZARDS:	AGENCY(IES) WITH WARNII	NGS:				
ACUTE AQUATIC	EU - GHS (H-Staten	EU - GHS (H-Statements)		H400 - Very toxic to aquatic life		
CHRON AQUATIC	EU - GHS (H-Staten	EU - GHS (H-Statements)		H410 - Very toxic to aquatic life with long lasting effects		
PHYSICAL HAZARD (REACTIVE)	EU - GHS (H-Staten	EU - GHS (H-Statements)		H250 - Catches fire spontaneously if exposed to air		
PHYSICAL HAZARD (REACTIVE)	EU - GHS (H-Staten	EU - GHS (H-Statements)		H260 - In contact with water releases flammable gases which may ignite spontaneously		
ENDOCRINE	TEDX - Potential En	TEDX - Potential Endocrine Disruptors		Potential Endocrine Disruptor		
MULTIPLE	German FEA - Subs	German FEA - Substances Hazardous to Waters		Class 2 - Hazard to Waters		

SUBSTANCE NOTES: Form-specific hazards not expected to apply to the finished and installed product; however, further processing (e.g. welding, sawing) during installation may release fumes or other respirable particles. The Safety Data Sheet (SDS) for Galvanized Sheet Steel can be found at http://cemcosteel.com/cemco-submittal-creator.



Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS

Inherently non-emitting source per LEED®

CERTIFYING PARTY: Self-declared

ISSUE DATE: 2018-10-01

EXPIRY DATE:

CERTIFIER OR LAB: N/A

APPLICABLE FACILITIES: City of Industry, CA 91746; Pittsburg, CA 94565; Denver, CO 80204; Fort Worth, TX 76140

CERTIFICATE URL:

CERTIFICATION AND COMPLIANCE NOTES: As per LEED: "Products that are inherently nonemitting sources of VOCs (stone, ceramic, powdercoated metals, plated or anodized metal, glass, concrete, clay brick, and unfinished or untreated solid wood) are considered fully compliant without any VOC emissions testing if they do not include integral organic-based surface coatings, binders, or sealants."

MULTI-ATTRIBUTE

Environmental Product Declaration (EPD) by UL

CERTIFYING PARTY: Third Party

APPLICABLE FACILITIES: City of Industry, CA 91746; Pittsburg, CA 94565; Denver, CO 80204; Fort Worth, TX 76140 CERTIFICATE URL:

ISSUE EXPIRY CERTIFIER OR

LAB: UL DATE: DATE: 2016-2021-

http://www.cemcosteel.com/sites/default/files/CEMCOs%20Environmental%20Product%20Declaration_EPD.pdf

07-13 07-13 Environment

CERTIFICATION AND COMPLIANCE NOTES: Declaration number: 4787356941.101.1. Environmental Product Declaration covers the following CEMCO Cold-Formed Steel Framing Systems, including: Structural Stud and Track (ICC-ES ESR 3016); ViperStud® Interior Framing (ICC-ES ESR 2620 & ATI-ES 0154); ProX Header® (IAPMO ER-0286); SureBoard® for Shear Panels (IAPMO ER- 0126); Sure-Span® Floor Joist Framing System (ESR PENDING); CST, SLP-TRK®, and FAS Track® 1000 Brand Slotted Tracks (ICC-ES ESR 2012); USG SHAFTWALL Brand CH and H-Stud Studs and Track (AER 09038); Expanded Metal Lath Products (ICC-ES ESR 1623); Plastering Accessories (ICC-ES ESR 1623); Drywall/Interior Accessories (ICC-ES ESR 3016); Connectors, Clips, and Channels (ICC-ES ESR 3016).



Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

GYPSUM WALLBOARD

HPD URL: https://www.hpd-collaborative.org/hpd-public-repository/

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES:

For installation of drywall framing system. According to ICC- ES ESR-2012: "The 5/8-inch-thick (15.9 mm), Type X gypsum wallboard must comply with ASTM C1396". Several domestic (USA) gypsum wallboard suppliers have published HPDs available for their products; see HPD Public Repository for more information and to download gypsum wallboard HPDs.

FASTENERS

HPD URL: No HPD available

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES:

Used to attach the tops of studs to CST/SLP-TRK®. According to ICC- ES ESR-2012: Fasteners "must be minimum No. 8 by 9/16-inch- long (14.3 mm), wafer-head, self-piercing tapping or self-drilling tapping, as applicable, steel screws complying with ASTM C 1513-13."



Section 5: General Notes

MANUFACTURER INFORMATION

MANUFACTURER: CEMCO

ADDRESS: 13191 Crossroads Pkwy. North

Suite 325

City of Industry CA 91746, USA WEBSITE: www.cemcosteel.com

CONTACT NAME: Fernando Sesma
TITLE: Director of Technical Services

PHONE: **800.416.2278**

EMAIL: fsesma@cemcosteel.com

KEY

OSHA MSDS Occupational Safety and Health Administration Material Safety Data Sheet
GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Hazard Types

AQU Aquatic toxicity

CAN Cancer

DEV Developmental toxicity **END** Endocrine activity

EYE Eye irritation/corrosivity

GEN Gene mutation

GLO Global warming

MAM Mammalian/systemic/organ toxicity

MUL Multiple hazards
NEU Neurotoxicity
OZO Ozone depletion

PBT Persistent Bioaccumulative Toxic

PHY Physical Hazard (reactive) REP Reproductive toxicity RES Respiratory sensitization

SKI Skin sensitization/irritation/corrosivity

LAN Land Toxicity

NF Not found on Priority Hazard Lists

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)

BM-3 Benchmark 3 (use but still opportunity for improvement)

BM-2 Benchmark 2 (use but search for safer substitutes)

BM-1 Benchmark 1 (avoid - chemical of high concern)

BM-U Benchmark Unspecified (insuficient data to benchmark)

Recycled Types

PreC Preconsumer (Post-Industrial)

PostC Postconsumer

Both Both Preconsumer and Postconsumer

Unk Inclusion of recycled content is unknown

None Does not include recycled content

LT-P1 List Translator Possible Benchmark 1 LT-1 List Translator Likely Benchmark 1

LT-UNK List Translator Benchmark Unknown (insufficient information from List Translator lists to benchmark)

NoGS Unknown (no data on List Translator Lists)

Other Terms

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material Nested Method / Product Threshold Substances listed within each material per threshold indicated per product Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology

Third Party Verified Verification by independent certifier approved by HPDC

Preparer Third party preparer, if not self-prepared by manufacturer

Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is
 delivered for end use.

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.